

Domes - Lillian

Dome Sizes	8"	450 lumens	4 lbs / 2 kg	9W
	10"	500 lumens	6 lbs / 3 kg	10W
	12"	900 lumens	8 lbs / 4 kg	18W
	14"	1200 lumens	10 lbs / 5 kg	24W
	18"	1800 lumens	14 lbs / 6 kg	36W
	22"	2100 lumens	18 lbs / 8 kg	42W
Standard Light	120V G8 LED Bulbs by Emery Allen. Color accuracy 90+ CRI. Choose from 2700K or 3000K light temperature. POWER: 120V. No transformer required. Compatible with most LED and incandescent dimmers. See details.			
Dim-To-Warm (Optional Upgrade)	12V GY6.35 Bulbs by Emery Allen. Color accuracy 90+ CRI. 1800K-2700K CCT light temperature. Light output reduced by up to 35%. Not available for 8" domes. POWER: 12V LED transformer required. Choose from: - Emery Allen Integrated Driver (installed in fixture canopy) - Remote Driver (installed in attic, basement, or closet) See LED Drivers & Dimmers.			
Premium Light (Optional Upgrade)	24V LED Strip by ElementalLED or QTL. Color accuracy 95+ CRI. Choose from light temperatures 2400K to 5000K. Inquire for premium Dim-To-Warm options. 50K+ hour lifetime (17+ years at 8 hr/day). Electrician replaceable. POWER: 24V LED transformer required. Choose from: - SwitchEX+ Driver/Dimmer Wall Unit (driver is in wall dimmer) - Remote Driver (installed in attic, basement, or closet) See LED Drivers & Dimmers.			
Custom Light	You may optionally specify your own LED strip and driver.			

Finishes	See Porcelain & Metal Finishes. Darker porcelain finishes diminish light output.
Production	Handmade in Boulder, Colorado. 8-12 week lead time. Rush by request.
Mounting	Standard junction box. Sloped ceiling by request. See Canopy Options.

